



Manufacturer of the First FAA Sign in 1955

VA Loading & Power Factors

Certified to current FAA Advisory Circular 150/5345-44

Specification for Runway and Taxiway Signs

View our Certificate of Conformance

		FAA Style 2 (4.8A-6.6A) FAA Style 3 (2.8A-6.6A)			FAA Style 5 (5.5A)		
SIGN SIZE & MODULE LENGTH	LAMPS	4W LED			4W LED		
		ISO XFMR	MAX VA	POWERFACTOR	ISO XFMR	MAX VA	POWERFACTOR
Size 1, 1-mod	2	100W	49	.94	100W	37	.94
2-mod	4	100W	64	.88	100W	48	.89
3-mod	6	100W	67	.89	100W	50	.90
4-mod	8	100W	73	.90	100W	56	.91
Size 2, 1-mod	3	100W	62	.87	100W	46	.88
2-mod	6	100W	67	.89	100W	50	.90
3-mod	9	100W	74	.90	100W	58	.92
4-mod	12	100W	78	.91	100W	62	.93
Size 3, 1-mod	3	100W	62	.87	100W	46	.88
2-mod	6	100W	67	.89	100W	50	.90
3-mod	9	100W	74	.90	100W	58	.92
4-mod	12	100W	78	.91	100W	62	.93
Size 5, 1-mod	3	100W	62	.87	100W	46	.88
Size 4, 1-mod	6	100W	67	.89	100W	50	.90

		XTL Lighting Systems					
Sign Size & Module Length	Lamps	FAA Style 2 (4.8A-6.6A) XTL 20W Quartz			FAA Style 3 (2.8A-6.6A) XTL 20W Quartz		
		Isol Xfmr	Max VA	Pwr Factr	Isol Xfmr	Max VA	Pwr Factr
Size 1, 1-mod	1	100W	71	0.89	100W	71	0.89
2-mod	2	100W	79	0.93	200W	78	0.92
3-mod	3	200W	102	0.93	300W	107	0.91
4-mod	4	200W	127	0.93	300W	131	0.92
Size 2, 1-mod	2	100W	79	0.93	200W	78	0.92
2-mod	4	200W	127	0.93	300W	131	0.92
3-mod	6	300W	167	0.93	500W	174	0.92
4-mod	8	300W	214	0.94	600W**	222	0.93
Size 3, 1-mod	2	100W	79	0.93	200W	78	0.92
2-mod	4	200W	127	0.93	300W	131	0.92
3-mod	6	300W	167	0.93	500W	174	0.92
4-mod	8	300W	214	0.94	600W**	222	0.93
Size 5, 1-mod	2	100W	79	0.93	200W	78	0.92
Size 4, 1-mod	4	200W	127	0.93	300W	131	0.92

* For less than ideal circuits, we recommend an upsized transformer to ensure adequate power to the sign.

**A Siamese pigtail with two male L-823 plugs and one tennis ball female receptacle is supplied with these signs for connection to two isolation transformers making the required wattage sum.

Lumacurve Airfield Signs

9115 Freeway Drive, Macedonia, OH 44056
P: 800.258.1997 / 330.467.2030 F: 330.467.2076

www.lumacurve.com

12/2020
LED/XTL Load Chart



Manufacturer of the First FAA Sign in 1955

VA Loading & Power Factors

			Traditional Lighting Systems, Style 5					
			FAA Style 5 (Constant 5.5A)			FAA Style 5 (Constant 5.5A)		
Sign Size &		45W/T10P			45W EXM Qtz			
Module Length	Lamps	Isol Xfmr	Max VA	Pwr Factr	Isol Xfmr	Max VA	Pwr Factr	
Size 1, 1-mod	1	45W	33	0.99	45W	39	0.99	
	2-mod	2	100W	65	0.99	100W	71	0.99
	3-mod	3	100W	93	0.99	100W	101	0.99
	4-mod	4	200W	127	0.99	200W	141	0.99
Size 2, 1-mod	2	100W	65	0.99	100W	71	0.99	
	2-mod	4	200W	127	0.99	200W	141	0.99
	3-mod	6	200W	181	0.98	200W	192	0.98
	4-mod	8	300W	236	1.00	300W	261	1.00
Size 3, 1-mod	2	100W	65	0.99	100W	71	0.99	
	2-mod	4	200W	127	0.99	200W	141	0.99
	3-mod	6	200W	181	0.98	200W	192	0.98
	4-mod	8	300W	236	1.00	300W	261	1.00
Size 5, 1-mod		2	100W	65	0.99	100W	71	0.99
Size 4, 1-mod		4	200W	127	0.99	200W	141	0.99