



PART NUMBERING KEY

*Lumacurve Catalog Number
for complete signs*

FAA Certified Lighting Systems

Lumacurve lighted signs can be ordered using the multi-element part number below, which indicates sign size, module length, and lamp type.

FAA SIGN SIZE	MOD LENGTH	LAMP TYPE
S = Small (Size 1)	1	L = "LED"; 4W (Style 2: 4.8A-6.6A, Style 3: 2.8A-6.6A & St 5: 5.5A)
M = Medium (Size 2)	2	X = "XTL", 10V/20W Quartz (Style 2: 4.8A-6.6A and Style 3: 2.8A-6.6A)
L = Large (Size 3)	3	P = 45W/T10P; 4W (Style 5: 5.5A)
D = RDR (Size 4)	4	Q = 45W EXM Quartz (Style 5: 5.5A)
DL = RDR (Size 5)		
B = Size 4 Barrier Engagement Marker		

(Example: "S1X" = Size 1, 1 Module, (Style 2 or 3) 10V/20W Quartz Lamp)

Lighting Style: Style 2 and style 3 systems are available with "XTL" 20W Quartz & "L" 4W lamps in all sizes.

Style 5 systems are available with 45W/T10P, 45W EXM, or "L" 4W lamps in all sizes.

Class: All lighting systems are class 2 (operation from -40°F [-40°C] to 131°F [55°C] environment).

Mode: All lighted signs are available in mode 2 or 3 in accordance with FAA AC 150/5345-44.

Mode 2 (must withstand wind loads of 200 mph (322kph)).

Mode 3 (must withstand wind loads of 300 mph (483 kph)).

FAA Certified UL Series -Unlighted Sign

UL SIGN SIZE	HEIGHT	LENGTH
SUL-4 = Small (Size 1)	18"	4 = 4'
SUL-6 = Small (Size 1)	18"	6 = 6'
MUL-4 = Medium (Size 2)	24"	4 = 4'
MUL-6 = Medium (Size 2)	24"	6 = 6'
LUL-4 = Large (Size 3)	30"	4 = 4'
LUL-6 = Large (Size 3)	30"	6 = 6'

(Example: "MUL-4" = Size 2, 4 foot)

Mode: All unlit signs are available in mode 2 in accordance with FAA AC 150/5345-44.

Mode 2 (must withstand wind loads of 200 mph (322kph)).

LUMACURVE AIRFIELD SIGNS

9115 Freeway Dr., Macedonia, OH 44056
800-258-1997 www.lumacurve.com